



TECHNICAL DATA SHEET

CRC 808 Silicone



CRC 808 Silicone is a multi-purpose silicone spray for general lubrication. It leaves a thin, clear, odourless film that lubricates, waterproofs and revives without damaging treated surfaces or leaving marks or stains.

CRC 808 Silicone eliminates squeaking and binding caused by friction and is ideal for use on metals, plastics, rubber, fabrics, wood, glass and painted surfaces.

CRC 808 Silicone is an excellent mould release, parting agent, and machine bed lubricant. It provides ongoing protection over a wide range of temperatures.

Item Code: 3055

Pack Size: 330g Aerosol

Features and Benefits

- **Multi-Purpose product:** Revives, lubricates, waterproofs, cleans and shines
- **Clear, odourless, non-staining:** No need for messy greases and oils
- **Reduces friction and wear:** Reduces noise, extends product life, reduces downtime
- **Excellent mould release, parting agent, and machine bed lubricant**
- **Harmless to most materials:** Metals, plastics, rubber, adhesives, wood, fabrics, glass, inks and paints
- **Wide temperature range:** Effective from -38°C to 290°C

Applications

- **Automotive:** Door locks, hinges, linkages, window guides & bushes, rubber mouldings, weather strips, grommets, o-rings, rubber seals, dashboards, plastic parts and mountings
- **Industrial:** Studs, bolts and nuts, hoists, tracks, lifting gear and blocks, pumps, compressors, conveyor rollers and shutters
- **Home:** Sliding doors, locks, catches, curtain and shower tracks, drawer slides, castors, hinges, plastic rollers
- **Sports equipment:** Ski equipment, bicycles, skateboards, roller blades, roller skates, golf trundlers and all yacht rigging gear

Typical Properties and Characteristics

Flash Point	-10°C
Odour	Pleasant solvent odour
Appearance	Clear, water-white liquid
Solubility	Insoluble
Propellant	Hydrocarbon

Flammability	Extremely flammable
Boiling Point	80°C
Type of film	Clear oily film
Drying time	5 minutes
Specific Gravity	0.7



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au



TECHNICAL DATA SHEET

CRC 808 Silicone

Directions

1. Shake can well.
2. Hold the can 30cm away from a clean, dry surface.
3. Spray evenly onto the surface.
4. Use an extension tube for hard-to-reach areas.

Special Precautions

General:

Extremely Flammable aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Deliberately sniffing or inhaling concentrated contents can be harmful or fatal. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Dispose of contents/container in accordance with relevant regulations.

Pressurized container: may burst if heated. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries (Aust) Pty Ltd
9 Gladstone Road, Castle Hill
NSW 2154, Australia

www.crcindustries.com.au
PH: 1800 224 227
Email: info.au@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 06/2026



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au