



TECHNICAL DATA SHEET

CRC Long Life



CRC Long Life is a wet film anti-rust lubricant that provides superior lubrication and long-term rust prevention to all metals subjected to rust and salt corrosion.

CRC Long Life is an excellent lubricant for extending the life of metal-to-metal sliding/rotating surfaces. It is a clear, free-running fluid that is safe to use in most situations and easy to apply and remove if necessary.

CRC Long Life is recommended as a final film for precision machine surfaces and as a protective, anti-seize coating for assemblies in storage or shipment. It is also used as a start-up lubricant for stored machinery.

Item Code: 3097

Pack Size: 300g Aerosol

Features and Benefits

- **Long term corrosion protection:** Indoor protection up to 2 years - Great for storing products that can easily become rusted (freshly made steel products)
- **Self-healing properties:** High affinity for the metal surfaces
- **Safe to use on most surfaces** including rubber, fabric, plastics and paints
- **Contains no CFC's, chlorinated solvents or silicone**
- **Easy to remove:** Removes readily with CRC Lectra-Clean or CRC Brakleen
- **Easy to apply:** Aerosol for controlled application

Applications

- **Automotive/Reconditioning Workshop:** To preserve engine blocks, pistons and components from atmospheric rusting
- **Marine:** Ideal for seasonal "mothballing" marine engines and corrosion free storage
- **Sawmills/Machine Workshop:** To protect valuable cutting tools, dies and equipment
- Cables, chains, pulleys, elevator machines

Typical Properties and Characteristics

Flash Point	26°C
Odour	Mild odour
Appearance	Opaque Amber
Solubility	Insoluble in water
Type of film	Non-drying
Film Thickness	5-10 micron

% Volatile	58%
Vapour Density	Heavier than air
Relative Density	0.97
Flammability	Flammable
Propellant	Hydrocarbon
Coverage	50m ² /1L



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au



TECHNICAL DATA SHEET

CRC Long Life

Directions

1. DE-ENERGISE equipment before using.
2. Shake can well before spraying.
3. Apply liberally onto surface to be protected ensuring total surface is coated to give maximum protection. Use extension tube in hard-to-reach areas and spot lubrication.
4. Removal of film is not required before equipment start-up.
5. If required, remove CRC Long Life with CRC Brakleen, CRC Lectra-Clean or petroleum solvents.

Special Precautions

General:

Flammable aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Use with adequate ventilation. Deliberately sniffing or inhaling concentrated contents can be harmful or fatal. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Dispose of contents/container in accordance with relevant regulations.

Aerosol Cans:

Pressurized container: may burst if heated. Do not pierce or burn, even after use. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked-up. Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries (Aust) Pty Ltd
9 Gladstone Road, Castle Hill
NSW 2154, Australia

www.crcindustries.com.au
PH: 1800 224 227
Email: info.au@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 05/2026



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au