



TECHNICAL DATA SHEET

CRC Soft Seal



CRC Soft Seal is a premium heavy-duty, long-term, indoor/outdoor corrosion inhibitor for machined metal surfaces and assemblies subjected to long periods of storage or adverse shipping conditions.

CRC Soft Seal provides a dry transparent, amber waxy film for heavy protection of parts that will not wash or wipe off even in severe conditions.

CRC Soft Seal provides outdoor protection for up to 2 years. Ideal for protecting equipment during shipping even when exposed to salt spray and other corrosive conditions.

Item Code: 3013

Pack Size: 300g Aerosol

Features and Benefits

- Seals out moisture and corrosive contaminants
- Provides outdoor protection for up to 2 years
- Leaves a dry transparent waxy amber film
- Highly resistant to salt water & salt spray
- Easy to remove with CRC Brakleen or mineral spirits
- Never becomes brittle and will not craze

Applications

Ideal for use on protection & outdoor storage of followings.

- Metal parts and assemblies
- Heat pump exterior units and condensers
- Alloy extrusions
- Valves, cable end sealer, dies, moulds etc.

Typical Properties and Characteristics

Flash Point	26°C
Odour	Mild odour
Appearance	Viscous Opaque
Solubility	Insoluble in water
Type of film	Waxy, dry film
Viscosity (20°C)	200-500cP
Film thickness	20-50 micron

% Volatile	80%
Vapour Density	> Air
Specific Gravity	0.87
Flammability	Flammable
Propellant	Hydrocarbon
Coverage	20m ² /1L
Drying time	Approx. 1 hr to touch



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au



TECHNICAL DATA SHEET

CRC Soft Seal

Directions

1. DE-ENERGISE equipment before using.
2. Shake can well before spraying.
3. Mask area not to be sprayed.
4. Spray from a distance of 30-35 cm in light, even coats.
5. Additional coats for added protection may be applied after each coat dries.
6. When finished spraying, clean valve by turning can upside down and pressing actuator until only propellant escapes. If required, remove CRC Soft Seal with CRC Brakleen or mineral spirits.

Note: Best results are obtained when sprayed above 15° C.

Special Precautions

General:

Flammable aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Use with adequate ventilation. Deliberately sniffing or inhaling concentrated contents can be harmful or fatal. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Dispose of contents/container in accordance with relevant regulations.

Aerosol Cans:

Pressurized container: may burst if heated. Do not pierce or burn, even after use. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked-up. Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries (Aust) Pty Ltd
9 Gladstone Road, Castle Hill
NSW 2154, Australia

www.crcindustries.com.au
PH: 1800 224 227
Email: info.au@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 05/2026



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au