



TECHNICAL DATA SHEET

CRC Heavy Duty Parts Cleaner



CRC Heavy Duty Parts Cleaner is expertly engineered to deliver powerful, non-chlorinated cleaning performance - removing brake fluid, grease, oil, and stubborn contaminants quickly and safely.

Designed for precision and reliability, it restores brake linings, pads, drums, callipers, and industrial machinery to peak condition with ease.

Infused with selected solvents, this advanced formula features controlled evaporation, low surface tension, and high density to provide deep, effective cleaning. It penetrates and lifts embedded oil and grease from linings, ensuring a superior degreasing result every time.

Item Code: 5093

Pack Size: 400g Aerosol

Features and Benefits

- **Fast evaporation:** Minimises downtime associated with “clean-in-place” cleaning methods
- **Leaves no residue:** Prevents harmful build up and eliminates rinsing and wiping
- **Non-chlorinated, non-staining and non-corrosive:** Low toxicity
- **Controlled spray action:** Assists cleaning through surface agitation
- **Low surface tension:** Gives excellent penetration and ensures superior degreasing properties
- **Doesn't contain Methylene Chloride, Methyl Chloroform, Carbon Tetrachloride, and silicones**

Applications

- Automotive repair shops, heavy equipment maintenance, farm machinery and equipment, industrial machinery, diesel and petrol engines, power tools, air conditioning equipment and brake products.

Typical Properties and Characteristics

Flash Point	<10°C
Odour	Mild ethereal
Appearance	Clear colourless liquid
Solubility	Slightly soluble
Propellant	Hydrocarbon

Flammability	Extremely flammable
Boiling Point	40°C
% Volatile	100%
Vapour Density	>Air
Specific Gravity	1.07



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au



TECHNICAL DATA SHEET

CRC Heavy Duty Parts Cleaner

Directions

1. Equipment must be de-energised before cleaning.
2. For light cleaning, simply spray the surface and wipe away for a quick, effective clean.
3. For heavier build-up, thoroughly saturate the area and allow the formula to penetrate for 15–30 seconds. Reapply as needed, then wipe clean to reveal a residue-free finish.
4. Protect rubber components and painted surfaces from overspray to prevent damage.

Special Precautions

General:

Extremely Flammable aerosol. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on open flame or other ignition source. Use with adequate ventilation. Deliberately sniffing or inhaling concentrated contents can be harmful or fatal. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. Dispose of contents/container in accordance with relevant regulations.

Pressurized container: may burst if heated. Do not pierce or burn, even after use. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked-up. Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries (Aust) Pty Ltd
9 Gladstone Road, Castle Hill
NSW 2154, Australia

www.crcindustries.com.au
PH: 1800 224 227
Email: info.au@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd. All products should be tested for suitability on a particular application prior to actual use. CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 06/2026



TOGETHER, WE GET IT DONE.™

www.crcindustries.com.au