# TECHNICAL DATA SHEET

## *CRC Lectra Clean*

**CRC Lectra Clean** is a non-flammable heavy-duty evaporating cleaner and degreaser for use on electric motors and other heavy-duty electrical and mechanical equipment.

The stabilized fast-acting solvent blend effectively removes wax, grease, oil, dirt, moisture and foreign matter that are common causes of current leakages and electric inefficiencies. It minimizes downtime by cleaning low-voltage motors and equipment while in operation.

CRC Lectra Clean, as part of a regular maintenance programme, promotes increased operating efficiency and longer equipment life by cleaning and removing foreign substances that can cause leakage, excessive resistance and hazardous operation of electrical equipment.

**Item Code: 2023** **Pack Size: 20L Drum**

## Features and Benefits

- **Non-flammable and No flash point:** Significantly reduces the risk of fire caused by incidental contact
- **Rapid and complete evaporation:** Leaves no residue, no rinsing or wiping required
- **Non-conductive and Non-corrosive**
- **Can be used on energized equipment:** Minimizes downtime, spray on while in use
- **Quickly penetrates into hard-to-reach areas**
- **Contains no lubricants, silicones, oils**

## Applications

- Electrical equipment, parts and components
- Mechanical tools and components
- Marine and industrial engines
- Laboratory equipment

## Typical Properties and Characteristics

| | |
|---|---|
| Flash Point | None |
| Odour | Mild ethereal |
| Appearance | Colourless liquid |
| Solubility | Insoluble in water |
| ASTM D-1133 (Kauri-Butanol Value) | 130 |
| Dielectric Constant | 3.4 |

| | |
|---|---|
| Flammability | Non-flammable |
| Boiling Point | 86°C |
| % Volatile | 100% |
| Vapour Density | 4.5 |
| Specific Gravity | 1.51 |
| ASTM D-877 (Dielectric Strength) | 36,700 Volt |

## Directions

1. Remove access plates to expose equipment interior. For heavy deposits, remove by scraping.
2. Apply liberally and allow to run off.
3. Air dry or dry with soft wiper.
4. Repeat the application if necessary.

**Note:** Test on small area before using. May be harmful to some plastics.

## Special Precautions

**General:**
Causes skin and serious eye irritation. Toxic to aquatic life with long lasting effects. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Dispose of contents/container in accordance with relevant regulations.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Take off contaminated clothing and wash it before reuse. Wash thoroughly after handling. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Refer to **Safety Data Sheet** for more details.

## Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

## Contact Information

**CRC Industries (Aust) Pty Ltd**
9 Gladstone Road, Castle Hill
NSW 2154, Australia

**www.crcindustries.com.au**
PH: 1800 224 227
Email: info.au@crcind.com

**Disclaimer:** All information on this data sheet is based on testing by CRC Industries (Aust) Pty Ltd.
All products should be tested for suitability on a particular application prior to actual use.
CRC Industries (Aust) Pty Ltd makes no representations or warranties of any kind concerning this data.