Style C 6.3 (1/4").



7013 Z **Standard bit, hex, style C 6.3.**

Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style C 6.3.
Application: For all types of screw applications in trade and industry.

Order-No.			
04011	1.5	25	10
01703	2.0	25	10
01704	2.5	25	10
01705	3.0	25	10
01706	4.0	25	10
01707	5.0	25	10
01708	6.0	25	10
01709	8.0	25	10
01710	10.0	25	10



7013R Z **Standard bit, hex, style C 6.3.**

Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style C 6.3.
Application: For all types of screw applications in trade and industry.
Insert screws into or remove from boreholes, especially in difficult to access areas.
Extra: MagicRing® made from spring steel holds all standard screws in every position.

Order-No.			
22955	3.0	25	10
22956	4.0	25	10
22957	5.0	25	10
22958	6.0	25	10



7013 Z TR **Standard bit, hex Tamper Resistant, style C 6.3.**

Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style C 6.3.
Extra: Hole in the tip of the bit for hex Tamper Resistant security screws.

Order-No.			
25560	TR2.0	25	10
25561	TR2.5	25	10
25562	TR3.0	25	10
25563	TR4.0	25	10
25564	TR5.0	25	10
26309	TR6.0	25	10
20558	TR5/64	25	10
20556	TR3/32	25	10
20559	TR7/64	25	10
20555	TR1/8	25	10
20560	TR9/64	25	10
20557	TR5/32	25	10
30050	TR3/16	25	10

Style C 6.3 (1/4").



7017 Z **Standard bit, ball end hex, style C 6.3.**

Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style C 6.3.
Application: For all types of screw applications in trade and industry.
Especially for screws that are difficult to access.
Ideal for window constructors.
Extra: The ball end enables the user to work at angles up to 25°.

Order-No.			
01734	1.5	38	10
01735	2.0	38	10
01736	2.5	38	10
01737	3.0	38	10
01738	4.0	38	10
01739	5.0	38	10
01740	6.0	38	10



7017R Z **Standard bit, ball end hex, style C 6.3.**

Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style C 6.3.
Application: For all types of screw applications in trade and industry.
Insert screws into or remove from boreholes, especially in difficult to access areas.
Extra: MagicRing® made from spring steel holds all standard screws in every position. Ball end allows a working angle up to 25°.

Order-No.			
22959	3.0	38	10
22960	4.0	38	10
22961	5.0	38	10
22962	6.0	38	10

Wiha Info



Wiha MagicRing®.

Spring steel ring reliably holds hex screws in place