

ALL METAL KEYLESS CHUCKS



Manufactured in Spain



Manufactured in Spain

Keyless Drill Chuck with metal body, locking mechanism and carbide jaw-inserts.
With a locking mechanism, no key is required for closing or opening, for hammer drilling and also screwdriver operations.
Carbide jaw-inserts (for 13mm capacity) reduce bit slippage and enhance wear resistance.
Ergonomic and strong design with full metal sleeves in black oxide finish that eliminate the possibility of rust.
With through hole for clockwise and anticlockwise rotation.
Supplied with screw M5 (R-3/8") or M6 (R-1/2") to fix chuck to drilling machine.
Fits any type of drill (up to 1000W) via UNF thread, male and female.
Wide range of accessories (see more info in our Price List)

Model	Capacity	MOUNT		SIZES MM	
No.	mm	K	O	L1	L2
CPM-10 R-3/8	1-10	3/8-24	41	54.5	64.5
CPM-10 R-1/2	1-10	1/2-20	41	54.5	64.5
CPM-13 R-3/8	2-13	3/8-24	43	62.5	74.5
CPM-13 R-1/2	2-13	1/2-20	43	62.5	74.5

Light-Duty Drill Chuck with key for portable drilling machines.
Ideal for electric portable drilling machines, with or without batteries, cutting direction reversible or non reversible.
Fits tools of up to 16mm.
Fits to machine via UNF screw fittings, male and female, DIN-238 and E-6.3.

Model	Capacity	MOUNT		SIZES MM		
No.	mm	K	Key	O	L1	L2
CL-06-ATOR	1 - 6.5	1/4 hex	LKC4	30	44	55
CL-06-R-3/8	1 - 6.5	3/8-24	LKC4	30	44	55
CL-10 R-1/2	1-10	1/2-20	KG	33	50	60
CL-10 R-3/8	1-10	3/8-24	KG	33	50	60
CL-13 B-16	1-13	B-16	S2	43	59	73
CL-13 R-1/2	1.5-13	1/2-20	S2	43	59	73
CL-13 R-3/8	1.5-13	3/8-24	S2	43	59	73
CL-16 B-16	3-16	B-16	K3	54	66	66

DRILL CHUCKS - KEYED - BALL BEARING INDUSTRIAL

KEYED CHUCKS



Manufactured in Spain

Ball Bearing Drill Chuck with key for production drilling equipment.
Drill chuck with key for industrial applications that require the toughest machining conditions.
Equipped with ball bearings to reduce friction in the tightening mechanism and provide a better grip on the drill shaft.
All the pieces are hardened and ground.
The one piece gear ring and sleeve eliminate the possibility of tooth breakage.
Fits tools of up to 25mm (1"), machine fitting via Jacobs tapers.

Model	Capacity	Mount		Sizes	mm		Equivalent
No.	mm	K	Key	O	L1	L2	size
CBB-08 J2	1-8mm	J-2S	LK30SB	47	55	70	-
CBB-10 J2	1-10mm	J-2S	LK32S9	47	55	70	11N
CBB-13 J3	1-13mm	J-3	LS3	62	75	94	14N
CBB-13 J6	1-13mm	J-6	LS3	62	75	94	-
CBB-16 J3	1-16mm	J-3	LK4S13	67	81	102	16N
CBB-19 J4	1-19mm	J-4	LK4S13	75	99	125	18N
CBB-25 J5	5-25mm	J-5	LK5	93	112	147	20N