







BLADES AND APPLICATIONS

CERAMIC & HSS SOLUTIONS




CERAMIC BLADES

All Noga **CR** blades are manufactured from high-performance ceramic material. Hardness: 1400-1700 HV.

Cat. No.	Blade Image	Edge	Application
CR2200		Straight	 
CR2500		Radius	 
CR5100		Double Burr	


SCRAPER

The Noga scraper blade is manufactured from HSS. Hardness: 63 Rc.

Ordering Cat. No.	Cat. No.	Blade Image	Angle	Material	Application
BD5010	D50		60°	HSS M2	 

HSS BLADES

Noga **HSS** blades are manufactured from HSS. Hardness: 62-64 Rc except N10 cobalt 65-66Rc.

BLADE	PICTURE	INCLUDED ANGLE	MATERIAL	HARDNESS	ORDERING CAT NO.	ABS	POLYACETAL	P.E	P.P	K-RESIN	P.C	POLYAMIDE	P.S	P.V.C
S BLADES HEAVY DUTY Ø 3.2mm														
S100		45°	HSS M35	65 Rc	BS1018	■	■	■	■	■	■	■	■	
S150		45°	HSS M2	63 Rc	BK3010		■	■	■	■	■		■	■
S150 TiN		45°	HSS M2	63 Rc	BK3103	■	■	■	■				■	
S10		40°	HSS M2	63 Rc	BS1010				■	■	■	■	■	■
S20		60°	HSS M2	63 Rc	BS2010		■	■	■				■	■
N BLADES LIGHT DUTY Ø 2.6mm														
N10P		35°	HSS M35	65 Rc	BN1410		■	■	■			■	■	■
N10		45°	HSS M35	65 Rc	BN1310	■		■	■	■	■	■	■	
N2		80°	HSS M2	63 Rc	BN2010			■	■			■	■	■
N1		40°	HSS M2	63 Rc	BN1010				■	■	■	■	■	■
N1 TiN		40°	HSS M2	63 Rc	BN1012	■	■	■	■		■			

■ First Choice

■ Second Choice