

HEAVY DUTY

- **Clamping Force (C):**
2,200 kg
- **Throat Depth (B):** 180 mm
- **Rail Size (D):** 42 x 19 mm
- **Tapped Hole (E):** M10
- Heavy Duty Pads

PN	A (mm)	Weight (kg)	4-IN-1 Part No.	Weight (kg)
UP125M	318	5.5	-	-
UP165M	419	6.2	-	-
UP205M	521	6.8	UP205M-C3	7.3
UP245M	622	7.5	-	-
UP405M	1,020	10.0	-	-
UP605M	1,537	12.7	-	-

MEDIUM DUTY

- **Clamping Force (C):**
350 - 1,100 kg
- **Tapped Hole (E):** M10
- Comfort Handle for G rail and M rail
- Spring Stop

PN	A (mm)	B (mm)	C (kg)	Standard Pad	Weight (kg)	4-IN-1 Part No.	Weight (kg)
UM205M	521	140	1,100	Heavy Duty	4.0	UM205M-C3	4.5
UM165M	419	140	1,100	Heavy Duty	3.6	UM165M-C3	4.0
UM125M	318	140	1,100	Heavy Duty	3.3	UM125M-C3	3.6
UM125PM	318	140	1,100	√	3.2	-	-
UM105M	267	140	1,100	Heavy Duty	3.1	-	-
UM105PM	267	140	1,100	√	3.0	UM105PM-C3	3.4
UM85M	216	140	1,100	Heavy Duty	2.9	UM85M-C3	3.2
UM85PM	216	140	1,100	√	2.8	UM85PM-C3	3.0
UM65M	165	140	1,100	Heavy Duty	2.5	-	-
UG205M	521	120	550	√	2.2	UG205M-C3	2.4
UG125M	318	120	550	√	1.8	UG125M-C3	2.1
UG85M	216	120	550	√	1.6	UG85M-C3	1.9
UF100M	254	120	460	√	1.3	-	-
UF65M	165	120	460	√	1.1	UF65M-C3	1.3
UE125M	318	100	380	√	1.2	-	-
UE85M	216	100	380	√	1.1	-	-
UG1657M	419	180*	350	√	3.0	-	-
UG1257M	318	180*	350	√	2.7	UG1257M-C3	2.9

* Deep Throat

LIGHT DUTY

- **Clamping Force (C):**
230 KG
- **Throat Depth (B):**
83 mm
- **Rail (D):** 16 x 8 mm
- **Tapped Hole (E):** M8
- Standard Pad
- Key Ring Stop

PN	A (mm)	Weight (kg)	4-IN-1 Part No.	Weight (kg)
UD85M	216	0.6	-	-
UD65M	165	0.5	UD65M-C3	0.7
UD45M	114	0.4	UD45M-C3	0.6