INSIDE/OUTSIDE ANGLE MAGNETS

- Two magnets inside + double plates for maximum pull
- Narrow profile for use in tight spots.
- **MLD series features fixed angles:** 90°, 30°/60°.
- MLA series can be adjusted from 30° to 270°
- Angles Setting Pin, included in MLA series, sets the angle from 30°, 45° and 90°




MLA
Angle Adjustable



Demo Video

MLD
Fixed Angle









PN	Description	Height (mm)	Width (mm)	Thickness (mm)	Max. Pull Force (kg)	Weight (kg)
MLDT350	Combo Pack, 1x MLD300 + 1x MLD500 *(MLD300 and MLD500 not to be sold separately)*					0.5
(MLD300) *(MLD500)*	*Fixed Angle, 90°, 30°/60°*	*76* *125*	*52* *85*	*14* *18*	*9* *15*	
MLD600	Fixed Angle, 90°, 30°/60°	165	110	20	18	0.8
MLA450	Adjustable Angle, 30 ~ 270°	120	120	18	12	0.5
MLA600	Adjustable Angle, 30 ~ 270°	156	156	20	15	0.9

CORNER MAGNETS, TWIN PACK

- Create 90° corners by holding from the outside, providing you with an unobstructed area for inside tack welds.
- One side corner "relief" provides clearance for tall lips.
- Use the outer edges of the Corner Magnet for setting up materials at 60°.



The compact and low profile Corner Magnet is ideal for light duty holding of stock at 90°.



Use the outer edges of the Corner Magnet to hold stock at 120°.

PN	Description	Dimension (mm)	Max. Pull Force (kg)	Weight (kg)
MST327	Twin Pack 90° & 60°	83 x 95 x 16	14	0.4