THE THIRD HAND MODULAR CLAMPS

"Third Hand" positions your workpiece at any angle for full weld access. Use your THIRD HAND to elevate and firmly hold stock at the ideal angle and height while you weld, cut, sand or paint.

Securely hold stock at any position with ball joint adjustment and locking.

- Universal clamp base mounts on flat or square surfaces (up to 50 mm thick), angle iron, and 25 mm round posts.
- 19 mm opening Slotted Adaptor Head accepts Pliers or Clamps to hold round, flat, square or angled stock. Two screws securely hold parts or clamps in position.



PN	Weight (kg)
HAS42	1.1



HAS42
w/ Universal Clamp Base

SNAKE MAGNETS

The Third Hand - *Holds, Bends, Twists*

The Snake Magnet gives you the flexibility to hold stock at odd angles.

MFC312 has two magnetic V-Pads that are adjustable for different shapes: round, flat, angle metal surfaces. Spring Clamp (included) can be used as the third hand to hold tools.





PN	Description	Weight (kg)
MFC312	300 mm flex cable, 1 clamp, 2 Adjustable Magnetic V-pads	0.5

MAGHOLD™ EXTENDABLE ARM

NEW ITEM

Extendable arm with magnetic pads on both ends for a secure hold on ferrous surfaces, turning any space into a flexible workspace.

- **Quick Adjustment:** 76 mm slot and cam bolts for fast, secure locking.
- **Smooth Pivoting:** Three cam bolts allow precise positioning.
- **Extendable Reach:** Adjusts from 200 mm to 280 mm with central pivot joint.







PN	Max. Pull Force (kg)	Break-away Force (kg)	Weight (kg)
MDP200	18 (ea.)	2.7 (ea.)	1.1

