PULL-STROKE SAWS

ALUMINIST® G-SAW™

JAPANESE-STYLE TEMPERING · MICRO WAVE IMPULSE HARDENED TOOTH · FLUORO COAT BLADE · 4×4 TEETH™ · Extra Thick* 0.04" (0.9mm)

- Tapered 9 TPI Fluoro-Coat blades
- Die-cast aluminum handle with elastomer grip
- Available in fixed-blade with sheath or folding handle models



ALOR-A240





ITEM CODE	BLADE LENGTH	TOOTH PITCH	TPI	BLADE THICKNESS / KERF WIDTH	CASE	MASTER CARTON	UPC
ALOR-A240	9.4 in (240 mm)	0.1 in (3.0 mm)	9 TPI	0.05 in. (1.2 mm)	4	24	0-49296-01741-5

G-SAW™ 240 / 210

JAPANESE-STYLE TEMPERING · MICRO WAVE IMPULSE HARDENED TOOTH · 4×4 TEETH™

- Multi-purpose 9 TPI blades
- Folding handle
- Elastomer grip



GK-G240



GK-G210





ITEM CODE	BLADE LENGTH	TOOTH PITCH	TPI	BLADE THICKNESS / KERF WIDTH	CASE	MASTER CARTON	UPC
GK-G240	9.4 in (240 mm)	0.1 in (3.0 mm)	9 TPI	0.03 in. (0.7 mm)	6	60	0-49296-01589-3
GK-G210	8.3 in (210 mm)			0.04 in. (1.0 mm)			0-49296-01575-6

California Proposition 65 warning applicable to all products on this page.

⚠ **WARNING** : Risk of cancer and reproductive harm from exposure to Di (2-ethylhexyl) phthalate (DEHP). See www.P65Warnings.ca.gov.