

**Safety Notice:**

Wiha ESD screwdrivers are noninsulated, therefore not suitable for working on live parts.

**Torque ESD interchangeable blades.****2889 Torque ESD slotted interchangeable blade.**

For Wiha ESD torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Moulded with static dissipative, black plastic material.

Surface resistance $10^6 - 10^9$ ohms.

Standards: IEC 61340-5-1, DIN ISO 2380.

Application: For ESD applications where recommended torque settings are important.

Order-No.	⊖	⊕	⊗	↔	↔	max. Nm	🔧
26869	0.25	1.5	4	175	42	0.15	10
26870	0.4	2.0	4	175	42	0.4	10
26871	0.5	3.0	4	175	42	0.6	10
26872	0.6	3.5	4	175	42	1.1	10
26873	0.8	4.0	4	175	42	2.5	10

**2889 Torque ESD Phillips interchangeable blade.**

For Wiha ESD torque screwdrivers.

Blade: IEC 61340-5-1, DIN ISO 8764.

Order-No.	⊕	⊗	↔	↔	max. Nm	🔧
26877	PH000	4	175	42	0.4	10
26876	PH00	4	175	42	0.4	10
26875	PH0	4	175	42	0.9	10
26878	PH1	4	175	42	3.8	10

**2889 Torque ESD Pozidriv interchangeable blade.**

For Wiha ESD torque screwdrivers.

Blade: IEC 61340-5-1, DIN ISO 8764.

Order-No.	⊕	⊗	↔	↔	max. Nm	🔧
26879	PZ0	4	175	42	0.9	10
26880	PZ1	4	175	42	3.8	10

**2889 Torque ESD TORX® interchangeable blade.**

For Wiha ESD torque screwdrivers.

Blade: IEC 61340-5-1.

Application: Very slim blade diameter for hard-to-reach screws.

Order-No.	⊗	⊗	↔	↔	max. Nm	🔧
26881	T5	4	175	42	0.4	10
26882	T6	4	175	42	0.6	10
26886	T7	4	175	42	0.9	10
26883	T8	4	175	42	1.3	10
26884	T9	4	175	42	2.5	10
26885	T10	4	175	42	3.8	10

ESD bit holder and Torque Setter. Set.**2889 Torque ESD bit universal holder.**

For Wiha ESD torque screwdrivers.

Suitable for C 6.3 and E 6.3 (1/4") bits.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Surface resistance $10^6 - 10^9$ ohms.

Sleeve: Made of stainless steel, moulded with dissipative, black plastic material.

Application: For ESD applications where recommended torque settings are important.

Order-No.	⊖	⊗	↔	↔	🔧
27711	1/4	4	162	11	10

**288-900 Torque-Setter ESD.**

Setting tool for variable Torque ESD screwdrivers.

Included in every torque ESD screwdriver delivery.

Blade: Octagonal blade, through hardened, zinc-plated.

Handle: Made of static dissipative plastic material.

Standards: IEC 61340-5-1.

Supplement: Included in every torque screwdriver delivery.

Order-No.	↔	↔	🔧
27279	80	150	1

**2882 S10 TorqueVario®-S ESD torque screwdriver set, 13 pcs.**

Torque value can be set via window scale.

With universal bit holder and 10 straight-blade/Phillips/Poszdriv/TORX® Standard bits.

Handle: Model 0.8-2.0 Nm.

Torque infinitely adjustable with Torque-Setter setting tool (also supplied). Ergonomic multi-component handle, made of ESD-safe dissipative material.

Standards: IEC 61340-5-1.

EN ISO 6798, BS EN 26789, ASME B107.14M.

Accuracy: $\pm 6\%$, traceable to national standards.

Application: For ESD applications where recommended torque settings are important.

Order-No.	Series	🔧
27687	2882 S10	1
2882	TorqueVario®-S ESD, model 0.8-2.0 Nm	
2889	Torque ESD bit universal holder	
288-900	Torque-Setter ESD	
⊖	7010 Z	4.5x25 5.5x25
⊕	7011 Z	PH0x25 PH1x25
⊗	7012 Z	PZ0x25 PZ1x25
⊗	7015 Z	T7x25 T8x25 T9x25 T10x25

with scale