

For hex nuts.

**341** SoftFinish® hex nut driver.**Round blade.**

Blade: Chrome-vanadium steel, through hardened, chrome-plated.
Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 3125.

Application: Particularly suitable for dry applications.

Order-No.	Ø	↔	↔	↕	↕	↕
01018	4	125	236	30	6.9	10
01020	5	125	236	30	7.9	10
01021	5.5	125	236	30	7.9	10
01022	6	125	236	30	8.9	10
01023	7	125	243	36	10.9	10
01024	8	125	243	36	11.9	10
01025	9	125	243	36	12.9	10
01026	10	125	243	36	14.4	10
01027	11	125	249	41	15.9	5
01028	12	125	249	41	16.9	5
01029	13	125	249	41	18.4	5
01030	14	125	249	41	19.4	5
01031	15	125	249	41	21.9	5
01032	16	125	249	41	21.9	5
01033	17	125	249	41	23.4	5

**347** SoftFinish® hex nut driver.**Round blade with hex bolster.**

Blade: Chrome-vanadium steel, through hardened, chrome-plated.
Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 3125.

Application: Particularly suitable for dry applications.

Order-No.	Ø	↔	↔	↕	↕	↕
01092	7	125	10	238	36	11.0
01093	8	125	10	238	36	12.0
01094	9	125	10	238	36	13.0
01095	10	125	10	238	36	14.5
01096	11	125	13	246	41	16.0
01097	12	125	13	246	41	17.0
01098	13	125	13	246	41	19.0

347 Zoll SoftFinish® hex nut driver. Inch sizes.**Round blade with hex bolster.**

Blade: Chrome-vanadium steel, through hardened, nickel-plated.
Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Application: Particularly suitable for dry applications.

Order-No.	Ø	↔	↔	↕	mm	↕	↕
02836	3/16	125	10	231	30	4.76	8
02837	1/4	125	10	238	36	6.35	10
02838	5/16	125	10	238	36	7.94	12
02839	3/8	125	10	238	36	9.53	14
02840	7/16	125	13	246	41	11.11	16
02841	1/2	125	13	246	41	12.70	19

For hex and triangular nuts.

**343** SoftFinish® hex nut driver.**Short round blade.**

Blade: Chrome-vanadium steel, through hardened, chrome-plated.
Deep drawn socket.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Application: For working in confined spaces.

Order-No.	Ø	↔	↔	↕	↕	↕
01076	5.5	65	176	30	8	10
01077	6	65	176	30	9	10
01078	7	65	183	36	11	10
01079	8	65	183	36	12	10
01081	10	65	183	36	14	10

**372** SoftFinish® hex nut driver.**Flexible shaft for hard to reach areas.**

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Application: E.g. for tightening and loosening adjustable hose clamps.

Order-No.	Ø	↔	↔	↕	↕	↕
01435	5	150	261	30	8	10
01436	5.5	150	261	30	8	10
01437	6	150	261	30	9	10
01438	7	150	268	36	11	10
01439	8	150	268	36	12	10
01440	10	175	293	41	14	10
01443	13	175	293	41	19	5

**344** SoftFinish® triangular nut driver.**Round blade.**

Blade: Chrome-vanadium steel, through hardened, chrome-plated.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.

Standards: DIN 22416.

Application: For triangular screws DIN 22424 and triangular nuts DIN 22425.

Order-No.	Ø	↔	↔	↕	↕	↕
26212	M4	125	6.8	236	30	11
26213	M5	125	8.3	236	30	13
26216	M6	125	10.05	236	30	16
26214	M8	125	12.05	243	36	18
26217	M10	125	15.05	243	36	22
26218	M12	125	16.55	249	41	24