

Wiha Classic.

The complete workshop range.

Combination pliers and high-leverage combination pliers.



Z 01 0 01 Classic combination pliers.

Standards: DIN ISO 5746.
Head shape: Extra long cutting edge for flat and round cables.
Design: OptiGrip - the newly designed gripping surface with 'triple-point support' ensures optimal hold of the workpiece while working. Cutting edges additionally induction hardened to approx. 64 HRC. The Wiha DynamicJoint® ensures optimal transmission of hand strength to the cutting edges.
Material: High quality C 70 tool steel, tempered.
Application: General purpose pliers for gripping and holding as well as cutting soft and hard wires and cables.

Order-No.	mm	II	○	●	●	g	SB	
26703	160	6 ½	3.1	2.0	1.6	160		5
27325	160	6 ½	3.1	2.0	1.6	160	x	5
26706	180	7	3.4	2.2	1.8	205		5
27336	180	7	3.4	2.2	1.8	205	x	5
26709	200	8	3.8	2.5	2.0	280		5
27337	200	8	3.8	2.5	2.0	280	x	5



Z 02 0 01 Classic high-leverage combination pliers.

Standards: DIN ISO 5746.
Head shape: Extra long cutting edge for flat and round cables.
Design: OptiGrip - the newly designed gripping surface with 'triple-point support' ensures optimal hold of the workpiece while working. Particularly powerful leverage results in 40% less effort being required for cutting tasks compared with standard combination pliers. Cutting edges additionally inductively hardened to approx. 64 HRC, therefore also appropriate for cutting piano wire. The Wiha DynamicJoint® ensures optimal transmission of hand strength to the cutting edges.
Material: High quality C 70 tool steel, specially tempered.
Application: Power assisted general purpose pliers for gripping and holding as well as cutting wires and cables ranging in hardness from soft to extremely hard.

Order-No.	mm	II	○	●	●	g	SB	
26712	200	8	3.8	2.8	2.3	275		5
27338	200	8	3.8	2.8	2.3	275	x	5
26715	225	9	4.2	3.0	2.5	330		5
27339	225	9	4.2	3.0	2.5	330	x	5

Needle-nose and round-nose pliers.



Z 05 0 01 Classic needle nose pliers with cutting edge.

Standards: DIN ISO 5745.
Head shape: Straight shape.
Design: Extra long cutting edge for flat and round cables. Gripping surfaces partially serrated in parts. Cutting edges additionally induction hardened to approx. 64 HRC.
Material: High quality C 70 tool steel, tempered.
Application: Gripping and holding as well as cutting soft and hard wires and cables. Preferred choice in the mechanical sector.

Order-No.	mm	II	○	●	●	g	SB	
26718	160	6 ½	2.5	1.8	1.2	120		5
27340	160	6 ½	2.5	1.8	1.2	120	x	5
26721	200	8	3.2	2.2	1.6	165		5
27341	200	8	3.2	2.2	1.6	165	x	5



Z 05 1 01 Classic needle nose pliers with cutting edge.

Standards: DIN ISO 5745.
Head shape: Angled, approx. 40°.
Design: Extra long cutting edge for flat and round cables. Gripping surfaces partially serrated in parts. Cutting edges additionally induction hardened to approx. 64 HRC.
Material: High quality C 70 tool steel, tempered.
Application: Gripping and holding as well as cutting soft and hard wires and cables. Preferred choice in the mechanical sector.

Order-No.	mm	II	○	●	●	g	SB	
26723	160	6 ½	2.5	1.8	1.2	120		5
27342	160	6 ½	2.5	1.8	1.2	120	x	5
26725	200	8	3.2	2.2	1.6	165		5
27343	200	8	3.2	2.2	1.6	165	x	5


Wiha Info



Wiha DynamicJoint –
A new dimension in strength and durability

- **Innovative:**
Optimised joint construction
- **Effective:**
Low loss of force means less force needed for cutting
- **Permanent:**
Optimal performance even after thousands of cuts

Wiha Info



Opti-Grip – optimal grip
due to newly designed gripping surfaces

- **A firm hold:** The 'triple-point support' protects the workpiece from twisting or slipping.
- **Highly effective:** Optimum grip even with a large jaw opening – and at the same time significantly less force needed
- **A wide selection:** Now in standard Wiha combination pliers and high leverage combination pliers