

Wiha Precision ESD.

The static dissipative precision screwdriver.

For slotted, Phillips and Pozidriv screws.



272 Precision ESD slotted screwdriver.

Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Precision handle with rotating cap, surface resistance $10^6 - 10^9$ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	①	↔	⊕	●t	↔	↔	↔
07634	1.5	40	0.25	2.0	120	12.5	10
07635	2.0	40	0.40	2.0	120	12.5	10
07636	2.5	50	0.40	2.5	145	13.0	10
07637	3.0	50	0.50	3.0	145	13.0	10
07638	3.5	60	0.60	3.5	170	14.0	10
07639	4.0	60	0.80	4.0	170	14.0	10



273 Precision ESD Phillips screwdriver.

Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Precision handle with rotating cap, surface resistance $10^6 - 10^9$ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	⊕	↔	●t	↔	↔	↔
28053	PH000	40	2.0	120	12.5	10
07640	PH00	40	2.0	120	12.5	10
07641	PH0	50	3.0	145	13.0	10
07642	PH1	60	4.0	170	14.0	10



274 Precision ESD Pozidriv screwdriver.

Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Precision handle with rotating cap, surface resistance $10^6 - 10^9$ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	⊕	↔	●t	↔	↔	↔
07643	PZ1	60	4.0	170	14	10

For hex nuts and hex socket screws.



275 Precision ESD hex screwdriver.

Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Precision handle with rotating cap, surface resistance $10^6 - 10^9$ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	●	↔	↔	↔	↔
27707	0.7	40	120	12.5	10
27708	0.9	40	120	12.5	10
07644	1.3	40	120	12.5	10
07645	1.5	50	145	13.0	10
07646	2	50	145	13.0	10
07647	2.5	60	170	14.0	10
07648	3	60	170	14.0	10
32315	4	60	170	14.0	10



276 Precision ESD ball end hex screwdriver.

Dissipative handle, ESD-safe.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Wiha ChromTop® finish on tip for a perfect fit every time.

Handle: Precision handle with rotating cap, surface resistance $10^6 - 10^9$ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Extra: The ball end enables the user to work at angles up to 25°.

Order-No.	●	↔	↔	↔	↔
07649	1.5	50	145	13.0	10
07650	2	50	145	13.0	10
07651	2.5	60	170	14.0	10
07652	3	60	170	14.0	10



277 Precision ESD hex nut driver.

Dissipative handle, ESD-safe.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.

Handle: Precision handle with rotating cap, surface resistance $10^6 - 10^9$ ohms.

Standards: IEC 61340-5-1.

Application: For working on electrostatically sensitive components.

Order-No.	○	↔	↔	↔	↔	↔
32312	1.5	60	2.5	-	155	13.0
32313	2.0	60	2.9	-	155	13.0
07653	2.5	60	4.0	4.0	155	13.0
07654	3	60	5.0	5.0	155	13.0
07655	3.5	60	5.3	6.0	155	13.0
07656	4	60	5.5	6.0	155	13.0
32314	4.5	60	6.2	7.0	155	13.0
07657	5	60	6.8	7.0	155	13.0
07658	5.5	60	7.6	8.0	170	14.0