Machine-operated nut driver inserts.



7044 **Standard bit, socket-wrench insert, style E 6.3.**

Material: High grade chrome-vanadium steel, through hardened.
Drive: DIN 3126, ISO 1173, style E 6.3.
Application: For all types of screw applications in trade and industry.

Order-No.	○		
04514	5.0	55	5
04513	5.5	55	5
04512	6.0	55	5
04511	7.0	55	5
04510	8.0	55	5
04509	10.0	55	5
04508	13.0	55	5
04515	1/4	55	5
04516	5/16	55	5
04517	3/8	55	5



7044 M **Standard bit, nut driver insert, magnetic, style E 6.3.**

Application: For all types of screw applications in trade and industry.
Extra: With strong permanent magnet.

Order-No.	○		
04637	5.0	55	5
04636	5.5	55	5
04635	6.0	55	5
04634	7.0	55	5
04633	8.0	55	5
04632	10.0	55	5
04631	13.0	55	5
04638	1/4	55	5
04639	5/16	55	5
04640	3/8	55	5



24632 **T-handle.**

Material: High-quality chrome-molybdenum steel, through-hardened, chrome-plated and polished.
Drive: DIN 3120.
Application: For hand used nut driver sockets.

Order-No.	▣		
32557	1/4	115	1



24635 **Universal joint (hand operation).**

Material: High-quality chrome-molybdenum steel, through-hardened, chrome-plated and polished.
Drive: DIN 3123.
Application: For working in hard-to-reach places with hand-operated nut drivers.
Extra: Easier joint operation.

Order-No.	▣	○		
32555	1/4	1/4	33	1

For nut driver inserts and bits



24630 **Ratchet with SoftFinish handle.**

Design: Ratchet wheel with 20 teeth, extremely smooth-running and resilient. With proven Wiha SoftFinish® multi-component handle for more safety when working.
Material: High-quality chrome-molybdenum steel, through-hardened, chrome-plated and polished.
Drive: DIN 3122, style D 6.3.
Application: For hand-operated nut driver inserts.
Extra: The locking button ensures secure holding of the nut driver and quick release of the attached tool.

Order-No.	▣		
32629	1/4	140	1



24631 **Ratchet with joint and SoftFinish handle.**

Design: Ratchet wheel with 20 teeth, extremely smooth-running and resilient. With proven Wiha SoftFinish® multi-component handle for more safety when working.
Material: High-quality chrome-molybdenum steel, through-hardened, chrome-plated and polished.
Drive: DIN 3122, style D 6.3.
Application: The articulated head makes working in hard-to-reach places with nut drivers easier.
Extra: The locking button ensures secure holding of the nut driver and quick release of the attached tool.

Order-No.	▣		
32630	1/4	165	1



SB 2463 001 **1/4" bit ratchet, with thumb wheel.**
Blister packed for hanging.

Design: Drop forged, especially robust version.
Maximum ergonomics due to user-specific SoftFinish form.
Finely serrated ratchet mechanism with 72 teeth.
Clockwise and anticlockwise direction can be switched via switching lever.
with practical thumb wheel.
Bit holder: For bits according to DIN 3126, ISO1173, style C 6.3 and E 6.3.
Material: High-quality chrome-molybdenum steel, chrome-plated and satin finished.
Application: Especially handy bit ratchet for a wide variety of fastening applications.
Minimum switching angle of only 5° enables use of bit ratchet even in the tightest spaces.
Due to outstandingly smooth running the mechanism functions even when other ratchets fail, e.g. with furniture assembly.
Extra: Thumb-wheel aids applying, fastening and releasing screws.

Order-No.	▣		
36931	1/4	90	5