

For Allen screws (inch).


369R Zoll Ball end hex L-key, long.
With MagicRing®. Inch sizes.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.
Standards: Based on ASME B18.3.
Application: Insert hex inch screws into and remove from boreholes, especially in difficult to access areas.
Extra: MagicRing® made from spring steel holds all standard screws tight at various angles (available from 1/8").
The ball end enables the user to work at angles up to 25°.

Order-No.	●	↔	↖	mm	↗
29471	0.05	72	13	1.27	10
29472	1/16	80	15	1.59	10
29474	5/64	88	18	1.98	10
29473	3/32	101	20	2.38	10
29475	7/64	111	21	2.78	10
24302	1/8	121	23	3.17	MagicRing® 10
24304	9/64	136	27	3.57	MagicRing® 10
24303	5/32	148	29	3.96	MagicRing® 10
24305	3/16	163	33	4.76	MagicRing® 10
24306	7/32	176	36	5.55	MagicRing® 10
24307	1/4	191	38	6.35	MagicRing® 10
24308	5/16	210	43	7.93	MagicRing® 10
24341	3/8	232	49	9.52	MagicRing® 10


369R HZ13 Hexagon ball end L-key set in ErgoStar holder.
From size 1/8" with MagicRing®, chrome-plated, 13 pc. inch design.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.
Standards: Based on ASME B18.3.
Application: Insert hex inch screws into and remove from boreholes, especially in difficult to access areas.
Extra: Mechanical operation of the space-saving ErgoStar holder makes simplest removal of each individual L-key possible without movement of the others.
MagicRing® made from spring steel holds all standard screws tight at various angles (available from 1/8").
The ball end enables the user to work at angles up to 25°.

Order-No.	Series	↗
36521	369R HZ13	5
●	369 Zoll C	0.05 1/16 5/64 3/32 7/64
●	369R Zoll	1/8 9/64 5/32 3/16 7/32 1/4 5/16 3/8

SB 369R HZ13 Hexagon ball end L-key set in ErgoStar holder.
From size 1/8" with MagicRing®, chrome-plated, 13 pc. inch design.
Blister packed. With practical wall bracket.

Order-No.	Series	↗
36522	SB 369R HZ13	5

For Allen screws (inch).


369R SZ13 Ball end hex L-key set in ProStar.
With MagicRing®, chrome-plated, 13 pcs. Inch sizes.

Blade: Chrome-vanadium steel, through hardened, chrome-plated.
Standards: Based on ASME B18.3.
Application: Insert hex inch screws into and remove from boreholes, especially in difficult to access areas.
Extra: Space saving ProStar allows the easy removal of each key without moving any others.
MagicRing® made from spring steel holds all standard screws tight at various angles (available from 1/8").
The ball end enables the user to work at angles up to 25°.

Order-No.	Series	↗
24190	369R SZ13	5
●	369 Zoll C	0.05 1/16 5/64 3/32 7/64
●	369R Zoll	1/8 9/64 5/32 3/16 7/32 1/4 5/16 3/8

SB 369R SZ13 Ball end hex L-key set in ProStar.
With MagicRing®, chrome-plated, 13 pcs. Inch sizes.
Blister packed.

Order-No.	Series	↗
24850	SB 369R SZ13	5



Wiha Info



Wiha ErgoStar

The right idea:
a flowing movement means
all L-keys are ready for removal.



reddot design award
winner 2010