Safety Notice:
When working with VDE tools, observe the national safety and accident prevention regulations!

1000 V IEC 60900:2012

TorqueVario®-S VDE. slimTorque VDE bit holder.

with scale



1000 V IEC 60900:2012

2872 **TorqueVario®-S VDE torque screwdriver.**
Insulation up to 1,000 V AC, GS-mark.
Torque value can be set via window scale. Automatic release.

Handle: Torque infinitely adjustable with Torque-Setter setting tool (also supplied).
Ergonomic multi-component handle, insulation up to 1,000 V AC, GS mark.
Handle sizes proportioned to optimise torque setting.
Audible and perceptible click when the pre-set torque has been attained.
Compatible with all blades of the 2831 series in connection with the bit holder (2879 series).
Standards: Manufactured acc. to IEC 60900:2012.
EN ISO 6798, BS EN 26789, ASME B107.14M.
Accuracy: ±6%, traceable to national standards.
Bit holder: slimTorque VDE bit holder (included in delivery) for 6 mm slimBits.
Application: For controlled fastening on live parts up to 1,000 V AC, for use only in combination with a slimTorque VDE bit holder for 6 mm slimBits.
Extra: Delivered in practical plastic box, incl. factory calibration certificate.
Individual: Products can be designed individually using the configurator at myto-rque.wiha.com. (Can be chosen freely: text field, torque unit)

Order-No.	Nm	±%				
26625	0.6-2.0	6%	3.8	131	30	1
26626	1.0-5.0	6%	3.8	138	36	1
26627	2.0-8.0	6%	3.8	142	41	1



1000 V IEC 60900:2012

2879 **slimTorque VDE bit holder for 6 mm slimBits.**
Insulation up to 1,000 V AC, GS-mark.
Exclusively for Wiha VDE torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish.
Insulation moulded directly onto blade.
Standards: Manufactured acc. to IEC 60900:2012.
Bit holder: Insulated metal ClicFix bit holder locks all slimBits reliability.
Only for 6 mm slimBits.
Application: For use of Wiha 6 mm slimBits with Wiha VDE torque screwdrivers.
Attention: Not for use with bit styles C 6.3 and E 6.3.

Order-No.					
35870	6	3.8	170	13	5

slimTorque starter set. Torque setter.

with scale



1000 V IEC 60900:2012

NEW
2872 S3 **slimTorque starter set, 5-pcs.**
Torque value can be set via window scale.
With slimTorque VDE bit holder for 6 mm slimBits.

Handle: VDE torque handle 1.0 - 5.0 Nm, steplessly adjustable with Torque Setter adjusting tool (included in delivery).
Bit holder: Insulated metal ClicFix bit holder locks all slimBits reliability.
Only for 6 mm slimBits.
Bits: Protective insulation moulded directly onto the bit and completely integrated into the bit in the lower area.
Individually tested protective insulation 1,000 V AC, VDE and GS tested.
Application: For controlled fastening on live parts up to 1 000 V AC.
Extra: 100% safety from fastening with torque according to specification of manufacturer type-tested switching devices according to EN 60439-1.

Order-No.	Series		
38074	2872 S3		1
	2872	TorqueVario®-S VDE, model 1.0-5.0 Nm	
	2879	slimTorque VDE bit holder for 6 mm slimBits	
	285-900	Torque-Setter	
	2831-14	SL/PZ1x75 SL/PZ2x75	



285-900 **Torque-Setter.**
Setting tool for variable torque screwdrivers.
Included in every torque screwdriver delivery.

Blade: Octagonal blade, through hardened, zinc-plated.
Supplement: Included in every torque screwdriver delivery.

Order-No.			
26864	150	80	1