Wiha T-handle torque tools.

For defined, strong fastening.

T-handle torque tools with scale.



with scale

2893 **TorqueVario®-STplus T-handle torque tool.**
Torque can be set via numerical scale.
With slipping clutch.

Handle: Window scale displays torque value numerically.
Torque infinitely adjustable with Torque-Setter setting tool (also supplied).
Soft-grip T-handle for extreme comfort and optimal torque transmission.
Audible and perceptible click when the pre-set torque has been attained.
Compatible with all blades of the 2899 series.
Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.
Accuracy: ±6%, traceable to national standards.
Application: For applications where recommended torque settings are important.
Use in combination with an interchangeable 6 mm blade for Wiha T-handle torque tools.
Extra: Delivered in practical plastic box, incl. factory calibration certificate.

Order-No.	Nm	○			
29233	5-14	6	56	120	1



with scale

2893 S01 **TorqueVario®-STplus T-handle torque tool set, 11 pcs.**
With bit universal holder, 6 TORX®/ hex Standard bits and 2 adapter blades for nuts.

Handle: Model 5-14 Nm.
Window scale displays torque value numerically.
Torque infinitely adjustable with Torque-Setter setting tool (also supplied).
Soft-grip T-handle for extreme comfort and optimal torque transmission.
Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.
Accuracy: ±6%, traceable to national standards.
Application: For applications where recommended torque settings are important.
Extra: Supply in robust box including works inspection protocol.

Order-No.	Series			
29234	2893 S01			1
	2893	TorqueVario®-STplus, model 5-14 Nm		
	289-900	Torque-Tplus Setter		
	2899	Torque-Tplus adapter blade		
	2899	Torque-Tplus bit quick release holder		
✱	7015 Z	T25x25	T30x25	T40x25
✺	7013 Z	4.0x25	5.0x25	6.0x25

Quick designs. Torque-Tplus Setter.



2891 **TorqueFix®-Tplus T-handle torque tool.**
With a fixed torque value pre-set by Wiha.
Automatic release. With slipping clutch.

Handle: Soft-grip T-handle for extreme comfort and optimal torque transmission.
Audible and perceptible click when the pre-set torque has been attained. Compatible with all blades of the 2899 series.
Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.
Accuracy: ±6%, traceable to national standards.
Application: For applications where recommended torque settings are important.
Use in combination with an interchangeable 6 mm blade for Wiha T-handle torque tools.
Extra: Delivered in practical plastic box, incl. factory calibration certificate.

Order-No.	Nm	○			
29228	6	6	56	120	1
29229	8	6	56	120	1
29230	10	6	56	120	1
29231	12	6	56	120	1
29236	12.5	6	56	120	1
29232	14	6	56	120	1



289-900 **Torque-Tplus Setter.**
Setting tool for variable T-handle torque tools.
Included in every T-handle torque tool delivery.

Blade: Octagonal profile with drilled tip, through hardened, zinc-plated.
Handle: Made of impact resistant cellulose acetate.

Order-No.			
28691	80	150	1