Wiha Bit holder with handle.

Bit holder 1/4".



384 **Bit holder with handle, magnetic, 1/4".**

Blade: Chrome-vanadium steel, through hardened, nickel-plated.
Handle: Wiha SoftFinish® multi-component handle with roll-off protection.
Bit holder: Stainless steel with strong magnet.
Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.

Order-No.					
01475	1/4	**125**	225	36	10
01476	1/4	**300**	400	36	5



386 **Bit holder with handle, flexible shaft, 1/4".**

Blade: Plastic coated flexible metal.
Handle: Wiha SoftFinish® multi-component handle with roll-off protection.
Bit holder: With retaining ring.
Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.
Application: For offset screws.

Order-No.					
01479	1/4	**150**	268	36	10



387 **Bit holder with handle, quick release holder, 1/4".**

Handle: Wiha SoftFinish® multi-component handle with roll-off protection.
Bit holder: ClicFix quick release holder, magnetic.
Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.
Application: Compact, handy style for working in confined spaces.
For applications where the bit must be held tight.

Order-No.					
25874	1/4	**35**	146	30	10



281-02 **Bit holder with handle, magnetic, 1/4".**

Handle: Wiha SoftFinish® multi-component handle with roll-off protection.
Bit holder: Stainless steel with strong magnet.
Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3 and E 6.3.
Application: Compact screwdriver together with bits, 1/4".
Together with Wiha countersink bits, can be used as manual deburrer.

Order-No.				
32160	1/4	**125**	36	10

Bit holder 1/4".



281 01 **Bit holder with handle, magnetic, 1/4".**

Handle: Ergonomic Wiha Stubby SoftFinish® handle, multi-component with roll-off protection.
Bit holder: Stainless steel with strong magnet.
Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.
Application: For working in confined spaces.
Extra: Together with Wiha countersink bits, can be used as manual deburrer.

Order-No.				
29463	1/4	**57**	34	10



281-01ESD **ESD bit holder with handle, retaining ring, 1/4".**
Dissipative handle, ESD-safe.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.
Surface resistance 10^6 - 10^9 ohms.
Universal use for all bits.
Standards: Handle: IEC 61340-5-1.
Output: For bits according to DIN 3126, ISO1173 style C 6.3.
Bit holder: Stainless steel with retaining ring.
Application: For working on electrostatically sensitive components, especially in tight places.

Order-No.				
32484	1/4	**57**	34	10



387ESD **ESD bit holder with handle, quick release holder, 1/4".**
Dissipative handle, ESD-safe.

Handle: Ergonomic Wiha SoftFinish® multi-component handle with roll-off protection.
Surface resistance 10^6 - 10^9 ohms.
Standards: Handle: IEC 61340-5-1.
Output: For bits according to DIN 3126, ISO1173 style C 6.3, E 6.3 and double bits.
Input: DIN 3126, ISO 1173, style E 6.3.
Bit holder: Stainless steel with retaining ring.
Application: For working on electrostatically sensitive components.
With integrated CentroFix bit holder, suitable for all bits and bit drills with the style C 6.3, E 6.3 or double bits.
Extra: True single-handed operation, extremely high retention force of bits (up to 20 kg) and virtually no play between bit and holder thanks to special closing and holding mechanism.

Order-No.					
32161	1/4	**38**	148	30	10