Warning:
6 mm slimBits only to be used in the slimVario bit holder and slimTorque VDE bit holder (VDE torque system).

1000 V IEC 60900:2012

SoftFinish® electric slimVario. slimBits.



1000 V IEC 60900:2012

2831-00 **SoftFinish® electric slimVario bit holder with handle and ClicFix, 6.0 mm.**

Blade: Chrome-vanadium steel, through-hardened. Insulation moulded directly onto blade.
Handle: Wiha SoftFinish® electric multi-component handle with roll-off protection.
Bit holder: Insulated metal ClicFix bit holder locks all slimBits reliability. Only for 6 mm slimBits.
Application: Compact screwdriver together with slimBits.
Attention: Not for use with bit styles C 6.3 and E 6.3.

Order-No.						
34577	6	30	50	160	13	5



1000 V IEC 60900:2012

2831-10 **SoftFinish® electric slimBit, slotted.**
Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Standards: Manufactured acc. to IEC 60900:2012.
Material: High-quality chrome vanadium steel, through-hardened, bronzed. Protective insulation moulded directly onto the bit and completely integrated into the blade in the lower area from size 4.0.
Application: For all work on or around electrical components up to 1,000 V AC.
Extra: The integrated protective insulation enables low-lying fastening and spring elements to be reached and manipulated. The slim form of the bit allows easy reaching of the screws below the finger and hand guards.
Attention: 6 mm slimBits only to be used in the slimVario bit holder and slimTorque VDE bit holder (VDE torque system).

Order-No.					max. Nm		
34578	2.5	75	0.4	6.0	0.4	no slim version	1
34579	3.0	75	0.5	6.0	0.6	no slim version	1
34580	4.0	75	0.8	6.0	2.5		1
34581	5.5	75	1.0	6.0	5.5		1
34582	6.5	75	1.2	6.0	5.5		1



1000 V IEC 60900:2012

2831-11 **SoftFinish® electric slimBit, Phillips.**
Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Order-No.				max. Nm	
34583	PH1	75	6.0	3.8	1
34584	PH2	75	6.0	5.5	1



1000 V IEC 60900:2012

2831-12 **SoftFinish® electric slimBit, Pozidriv.**
Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Order-No.				max. Nm	
34585	PZ1	75	6.0	3.8	1
34586	PZ2	75	6.0	5.5	1

slimBits.



1000 V IEC 60900:2012

2831-13 **SoftFinish® electric slimBit, Xeno, for terminal screws (slotted/ Phillips).**
Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Order-No.				max. Nm	
34587	SL/PH1	75	6.0	3.8	1
34588	SL/PH2	75	6.0	5.5	1



1000 V IEC 60900:2012

2831-14 **SoftFinish® electric slimBit, Xeno, for terminal screws (slotted/Pozidriv).**
Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Order-No.				max. Nm	
34589	SL/PZ1	75	6.0	3.8	1
34590	SL/PZ2	75	6.0	5.5	1



1000 V IEC 60900:2012

2831-15 **SoftFinish® electric slimBit, TORX®.**
Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Order-No.				max. Nm		
35506	T8	75	6.0	1.3	no slim version	1
35507	T10	75	6.0	3.8	no slim version	1
35508	T15	75	6.0	5.0		1
35509	T20	75	6.0	5.5		1
36071	T25	75	6.0	5.5		1



1000 V IEC 60900:2012

NEW
2831-18 **SoftFinish® electric slimBit, hexagon.**
Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Standards: High-quality chrome vanadium steel, through-hardened, bronzed. Protective insulation moulded directly onto the bit and completely integrated into the blade in the lower area from size 2.5.

Order-No.				max. Nm		
37222	1.5	75	6.0	0.9	no slim version	1
37223	2	75	6.0	1.8	no slim version	1
37224	2.5	75	6.0	3.8		1
37147	3	75	6.0	5.5		1
37225	4	75	6.0	5.5		1
37226	5	75	6.0	5.5		1
37227	6	75	6.0	5.5		1



1000 V IEC 60900:2012

2831-17 **SoftFinish® electric slimBit, square (Robertson).**
Individually tested protective insulation 1,000 V AC, VDE and GS tested.

Order-No.				max. Nm	
35510	Robertson 1	2.3	75	6.0	5.5	1
35511	Robertson 2	2.8	75	6.0	5.5	1