For Allen screws (metric).



334R **Hex driver with T-handle.**
With MagicRing®.

Blade: Chrome-vanadium steel, through hardened, nickel-plated.
Handle: Wiha Classic T-handle.
Application: For high torque transfer with minimal effort.
Extra: MagicRing® of spring steel (from size 3 mm) secures all hex standard screws independently of screw material in any position.

Order-No.	◉					
22168	3	100	126	80	26	10
22170	4	150	176	80	26	10
22172	5	150	182	100	32	10
22174	6	150	182	100	32	10
21960	8	200	232	100	32	10
21962	10	200	238	120	38	10

For Allen screws (metric).



540 **Ball end hex driver with T-handle.**

Blade: Chrome-vanadium steel, through hardened, nickel-plated.
Handle: Wiha Classic T-handle.
Application: For high torque transfer with minimal effort, especially for screws that are difficult to access.
Extra: The ball end enables the user to work at angles up to 25°.

Order-No.	◉					
04111	4	150	176	80	26	10
04108	5	150	182	100	32	10
04105	6	150	182	100	32	10
04099	8	200	238	100	32	10
04096	10	200	238	120	38	10



334R VB **Hex driver set with T-handle.**
With MagicRing®, in bench stand, 6 pcs.

Blade: Chrome-vanadium steel, through hardened, nickel-plated.
Handle: Wiha Classic T-handle.
Application: For high torque transfer with minimal effort.
Extra: MagicRing® made from spring steel holds all standard screws in every position. Robust metal workbench holder to place on workbench or wall-mount. Tip diagrams printed to scale.

Order-No.	Series				
22096	334R VB				1
◉	334R	3x100	4x150	5x150	
		6x150	8x200	10x200	

Wiha Info



Wiha MagicRing®.

Thanks to the Wiha MagicRing®, inserting and removing screws is safe and easy, even in areas that are difficult to access.