Wiha torque screwdrivers.

TorqueVario®-S with scale.



2852 **TorqueVario®-S Torque screwdriver.**
Torque value can be set via window scale.
Automatic release.

Handle: Torque infinitely adjustable with Torque-Setter setting tool (also supplied).
Ergonomic multi-component handle, particulary light and compact.
Handle sizes proportioned to optimise torque setting.
Audible and perceptible click when the pre-set torque has been attained.
Compatible with all blades of the 2859 series.
Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.
Accuracy: ±6%, tracing to national standards (see table for other tolerances).
Application: For applications where recommended torque settings are important.
Use in combination with a Wiha torque interchangeable blade.
Extra: Delivered in practical plastic box.
Incl. works inspection protocol.
Note: Bit holders or blades are not included in delivery.
Individual: Products can be designed individually using the configurator at mytorque.wiha.com.
(Can be chosen freely: text field, torque unit)

Order-No.	Nm	±%				
36849	0.04-0.46•	10%	4	127	23	1
26888	0.1-0.6	10%	4	127	23	1
36850	0.1-0.6	6%	4	127	23	1
26461	0.4-1.0	6%	4	127	23	1
26462	0.8-2.0	6%	4	131	30	1
26463	1.0-5.0	6%	4	138	36	1
26464	2.0-8.0	6%	4	142	41	1

• Precision in range of 0.1-0.46 Nm



285-900 **Torque-Setter.**
Setting tool for variable torque screwdrivers.
Included in every torque screwdriver delivery.

Blade: Octagonal blade, through hardened, zinc-plated.
Supplement: Included in every torque screwdriver delivery.

Order-No.			
26864	150	80	1

TorqueVario®-S sets.



2852 S10 **TorqueVario®-S Torque screwdriver set, 13 pcs.**
Torque value can be set via window scale.
With bit universal holder and 10 Phillips/ Pozidriv/ TORX®/ hex Standard bits.

Handle: Model 1.0-5.0 Nm.
Torque infinitely adjustable with Torque-Setter setting tool (also supplied).
Ergonomic multi-component handle, particulary light and compact.
Audible and perceptible click when the pre-set torque has been attained.
Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.
Accuracy: ±6%, traceable to national standards.
Application: For applications where recommended torque settings are important.
Extra: Supply in robust box.
Incl. works inspection protocol.

Order-No.	Series				
26893	2852 S10				1
	2852	TorqueVario®-S, model 1.0-5.0 Nm			
	2859	Torque bit universal holder			
	285-900	Torque-Setter			
	7011 Z	PH1x25	PH2x25		
	7012 Z	PZ1x25	PZ2x25		
	7015 Z	T10x25	T15x25	T20x25	T25x25
	7013 Z	3.0x25	4.0x25		



2852 S10-01 **TorqueVario®-S Torque screwdriver set, 13 pcs.**
Torque value can be set via window scale.
With bit universal holder and 10 TORX®/ TORX PLUS® Standard bits especially for applications with indexable cutter inserts.

Order-No.	Series				
34614	2852 S10-01				1
	2852	TorqueVario®-S, model 1.0-5.0 Nm			
	2859	Torque bit universal holder			
	285-900	Torque-Setter			
	7015 Z	T7x25 T15x25	T8x25	T9x25	T10x25
	7016 Z	7IPx25 15IPx25	8IPx25	9IPx25	10IPx25