TorqueFix® and Torque cable key.

2850 **TorqueFix® torque screwdriver.**
With a fixed torque value pre-set by Wiha.
Automatic release.

Handle: Ergonomic multi-component handle, particulary light and compact.
Handle sizes proportioned to optimise torque setting.
Audible and perceptible click when the pre-set torque has been attained.
Compatible with all blades of the 2859 series.
Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.
Accuracy: ±6%, traceable to national standards.
Application: For applications where recommended torque settings are important.
Use in combination with a Wiha torque interchangeable blade.
Extra: Delivered in practical plastic box, incl. factory calibration certificate.
Note: The below articles are available from stock. Further articles with pre-set, customer torque values of between 0.15 and 8 Nm are available on request. Bit holders or blades are not included in delivery.
Individual: Products can be designed individually using the configurator at mytorque.wiha.com. (Can be chosen freely: text field, torque unit, torque value)

Order-No.	Nm	±%				
26925	0.4	6%	4	112	23	1
26127	0.5	6%	4	112	23	1
26047	0.6	6%	4	112	23	1
26327	0.8	6%	4	112	23	1
26048	0.9	6%	4	112	23	1
26133	1.1	6%	4	119	30	1
26049	1.2	6%	4	119	30	1
26901	1.5	6%	4	119	30	1
26051	2.0	6%	4	119	30	1
26128	2.5	6%	4	119	30	1
26052	3.0	6%	4	126	36	1
26129	3.8	6%	4	126	36	1
26053	5.0	6%	4	132	41	1
26130	5.5	6%	4	132	41	1
34533	6.0	6%	4	132	41	1
26131	7.2	6%	4	132	41	1

2850 S2 **Torque cable key set for circular plug connectors.**
For Wiha torque screwdrivers.

Handle: TorqueFix® torque screwdrivers.
Ergonomic multi-component handle, particulary light and compact.
Material: Robust, glass-fibre reinforced plastic combines the high quality hexagonal stainless steel insert with the blade tang of chrome-vanadium-molybdenum steel.
Application: For controlled fastening of circular plug connectors with hexagonal head according to specified torque.

Order-No.	Nm		mm				
36846	0.4	9	230	78	112	23	1
36847	0.6	13	230	78	112	23	1
36848	1.5	22	240	90	119	30	1

easyTorque.

292 **easyTorque torque screwdriver.**
With a fixed torque value ex-factory.

Handle: Multi-component handle optimally designed for the hand enables optimal power transmission.
Audible and perceptible click when the pre-set torque has been attained. Rapid identification with imprint on handle end.
Unlimited loosening torque.
Mechanism insensitive to industrial lubricants.
Compatible with all blades of the 2859 series.
Accuracy: ±10%
Application: For applications where recommended torque settings are important.
Use in combination with a Wiha torque interchangeable blade.
Note: Bit holders or blades are not included in delivery.

Order-No.	Nm	±%				
36229	0.5	10%	4	130	34	1
36230	0.6	10%	4	130	34	1
36240	0.9	10%	4	130	34	1
36231	1.1	10%	4	130	34	1
36233	1.2	10%	4	130	34	1
36234	1.4	10%	4	130	34	1
36235	2.0	10%	4	130	34	1
36236	2.5	10%	4	130	34	1
36237	3.0	10%	4	130	34	1
36238	3.8	10%	4	130	34	1
36320	4.0	10%	4	130	34	1
36321	4.5	10%	4	130	34	1
36239	5.0	10%	4	130	34	1